View Section: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME:

3MTM Scotch-BriteTM Surface Conditioning Products, AMED (Sheets (HookitTM), Rolls, Discs (includes RolocTM, TN, TP, TR, TS, TSM), Belts,

Scrim Belts)

PRODUCT NAME:

3M Scotch-Brite Surface Conditioning Products, AMED (Sheets (HookitTM), Rolls, Discs (includes RolocTM, TN, TP, TR, TS, TSM), Belts,

Scrim Belts)

MANUFACTURER NAME: зм

DIVISION: **Abrasives Systems Division** ADDRESS: 3M Center St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

ISSUED: 03/23/10 SUPERSEDES: 07/29/09 Intended Use: **Abrasive Product** ADDRESS: 3M Center ADDRESS CITY: St. Paul. ADDRESS STATE: MN

ADDRESS ZIP: 55144-1000

BUSINESS PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

MSDS Manufacturer Number: 23-7148-2

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient Name	CAS#	Ingredient Percent
Aluminum Oxide Mineral	1344-28-1	25 - 40 by Weight
Filler	1317-65-3	3 - 6 by Weight
Additive	13463-67-7	< 2 by Weight
Nylon Backing	Mixture	10 - 20 by Weight
Nylon Scrim	None	5 - 10 by Weight
Cured Resin	Mixture	20 - 35 by Weight
RolocTM Attachment	None	0 - 5 by Weight
HookitTM Attachment	Mixture	0 - 5 by Weight

SECTION 3 - HAZARDS IDENTIFICATION

Specific Physical Form: Non-Woven Material Odor, Color, Grade:

General Physical Form: Solid

Immediate health, physical, and environmental hazards: This document covers only the 3M product. For complete assessment. when determining the degree of hazard, the material being abraded

must also be considered.

EYE CONTACT:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

SKIN CONTACT: Mechanical Skin irritation: Signs/symptoms may include abrasion,

redness, pain, and itching.

INHALATION: Dust from cutting, grinding, sanding or machining may cause irritation of

the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Prolonged or repeated exposure may cause: Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

INGESTION: No health effects are expected.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Flush eyes with large amounts of water. If signs/symptoms persist, get

medical attention.

SKIN CONTACT: Wash affected area with soap and water. If signs/symptoms develop,

get medical attention.

INHALATION: Remove person to fresh air. If signs/symptoms develop, get medical

INGESTION: No need for first aid is anticipated.

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed. First Aid Comments:

SECTION 5 - FIRE FIGHTING MEASURES

AUTOIGNITION Not Applicable

TEMPERATURE: FLASH POINT: Not Applicable FLAMMABLE LIMITS - LEL: Not Applicable FLAMMABLE LIMITS - UEL:

Not Applicable **EXTINGUISHING MEDIA:**

Material will not burn. Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam). Wear full protective equipment (Bunker Gear) and a self-contained SPECIAL FIRE FIGHTING breathing apparatus (SCBA).

PROCEDURES: UNUSUAL FIRE AND **EXPLOSION HAZARDS:**

Not applicable. None inherent in this product.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Not applicable. In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, $\frac{1}{2} \frac{1}{2} \frac{1}$

and federal regulations.

SECTION 7 - HANDLING and STORAGE

HANDLING: For industrial or professional use only. Avoid breathing of dust created

by sanding, grinding or machining. Avoid eye contact with dust or by sanding, grinding or machining. A void eye contact with dust or airborne particles. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. A lways wear eye and face protection when working at sanding or grinding operations or when near such operations. Sparks and particles flying from the product during sanding or grinding cap cause injury and fire

during sanding or grinding can cause injury and fire.

STORAGE: Store in a cool, dry place.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Ingredient: A dditive

Guideline Type: OSHA TWA, as total dust

Guideline Info: 15 mg/m3 **Guideline Info:** 5 mg/m3

Ingredient: **Aluminum Oxide Mineral Guideline Type:** OSHA TWA, as total dust

Guideline Info: 15 mg/m3 Ingredient: Filler

Guideline Type: OSHA TWA, respirable fraction

Guideline Info: 5 mg/m3 Ingredient: Filler

Guideline Type: OSHA TWA, as total dust

Guideline Info: 15 ma/m3

PETROLEUM DISTILLATES Ingredient:

Guideline Type: OSHA TWA **Guideline Info:** 2000 mg/m3 Ingredient: Additive **Guideline Type:** ACGIH TWA **Guideline Info:** 10 mg/m3 Additive Ingredient:

CMRG TWA, as respirable dust **Guideline Type:**

Guideline Info: 5 mg/m3

Ingredient: **Aluminum Oxide Mineral**

Guideline Type: CMRG TWA **Guideline Info:** 1 fiber/cc

Ingredient: Aluminum Oxide Minera OSHA TWA, respirable fraction **Guideline Type:**

Prevention of Swallowing: Not an expected route of exposure. Wash hands after handling and

before eating.

SOURCE OF EXPOSURE LIMIT

DATA:

ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American

Industrial Hygiene Association Workplace Environmental Exposure Level

(WEEL)

EYE PROTECTION:

A void eye contact. To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. The following eye protection(s) are recommended: Safety Glasses with side shields

SKIN PROTECTION: Avoid skin contact. Wear appropriate gloves to minimize risk of injury to

skin from contact with dust or physical abrasion from grinding or

sanding.

RESPIRATORY PROTECTION:

A void breathing of dust created by sanding, grinding or machining. Assess exposure concentrations of all materials involved in the wo process. Consider material being abraded when determining the appropriate resipratory protection. Select and use appropriate respirators to prevent inhalation overexposure. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with N95 particulate filters. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance

ENGINEERING CONTROLS: Use with appropriate local exhaust ventilation. Provide appropriate local

exhaust ventilation for sanding, grinding or machining. Provide ventilation adequate to control dust concentrations below recommended exposure limits and/or control dust. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control dust, fume, or airborne particles. If ventilation is not adequate, use respiratory protection equipment.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Odor, Color, Grade: Non woven abrasive

General Physical Form: Solid

Autoignition temperature: Not Applicable Flash Point: Not Applicable Flammable Limits - LEL: Not Applicable Flammable Limits - UEL: Not Applicable BOILING POINT: Not Applicable **VAPOR DENSITY:** Not Applicable VAPOR PRESSURE: Not Applicable SPECIFIC GRAVITY: Not Applicable Not Applicable MELTING POINT: Not Applicable

SOLUBILITY IN WATER: Not Applicable VISCOSITY: Not Applicable **Specific Physical Form:** Non-Woven Material Not Applicable Kow - Oct/Water partition

SECTION 10 - STABILITY and REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID:

10.1 Conditions to avoid None known 10.2 Materials to avoid None known

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

PRODUCTS:

HAZARDOUS DECOMPOSITION Substance: Carbon monoxide (Condition: During Combustion) Substance: Carbon dioxide (Condition: During Combustion)

PRODUCTS:

HAZARDOUS DECOMPOSITION Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another

material.

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicological Information:

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: CHEMICAL FATE INFORMATION:

Not determined.

Not determined.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in an industrial or commercial facility in the presence of a combustible material. Combustion products will include HF. Facility must be capable of handling halogenated materials. Since regulations vary, consult applicable regulations or authorities before disposal.

EPA Hazardous Waste Number EPA Hazardous Waste Number (RCRA): Not regulated

(RCRA):

SECTION 14 - TRANSPORT INFORMATION

Transportation Information:

Not regulated per U.S. DOT, IATA or IMO. These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15 - REGULATORY INFORMATION

US FEDERAL REGULATIONS:

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate

Hazard - Yes Delayed Hazard - Yes Contact 3M for more information.

STATE REGULATIONS: CHEMICAL INVENTORIES:

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements. Contact 3M for more

information.

INTERNATIONAL

Contact 3M for more information.

REGULATIONS:

Hazardous

WHMIS: U.S OSHA:

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16 - ADDITIONAL INFORMATION

NFPA - SPECIAL HAZARDS: None NFPA - REACTIVITY: 0 NFPA - HEALTH: 1 NFPA - FIRE: 0

HMIS AND NFPA NOTES:

NFPA Explanation: National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated. combustion or decomposition products that are known to be generated in significant quantities.;

Revision Changes:

Copyright was modified. Section 8: Skin protection phrase was modified. Section 8: Exposure guidelines ingredient information was modified. Section 9: Property description for optional properties was added. Section 10.1 Conditions to avoid was added. Section 10.2 Materials to avoid was added. Section 6: Release measures information was added. Section 10: Materials to avoid physical property was added. Section 10: Conditions to avoid physical property was added. Section 8: Skin/ hand protection phrase was added. Section 6: Release measures information was deleted. Section 10: Materials and conditions to avoid physical property was deleted. Section 8: Exposure guidelines legend was

DISCLAIMER

The information in this Material Safety Data Sheet (MSDS) is believed to

be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M. 3M MSDSs are available at www.3M.com