



Revision Number: 005.0

Issue date: 11/01/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

|                               |                                                                                          |                     |               |
|-------------------------------|------------------------------------------------------------------------------------------|---------------------|---------------|
| <b>Product name:</b>          | <b>LOCTITE 426 BLACK INSTANT ADHESIVE</b> known as <b>426 Prism® Black Max® Gel Inst</b> | <b>IDH number:</b>  | 229732        |
| <b>Product type:</b>          | Adhesive                                                                                 | <b>Item number:</b> | 18398         |
| <b>Restriction of Use:</b>    | None identified                                                                          | <b>Region:</b>      | United States |
| <b>Company address:</b>       | <b>Contact information:</b>                                                              |                     |               |
| Henkel Corporation            | Telephone: +1 (860) 571-5100                                                             |                     |               |
| One Henkel Way                | MEDICAL EMERGENCY Phone: Poison Control Center                                           |                     |               |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711                                             |                     |               |
|                               | TRANSPORT EMERGENCY Phone: CHEMTREC                                                      |                     |               |
|                               | 1-800-424-9300 (toll free) or 1-703-527-3887                                             |                     |               |
|                               | Internet: www.henkelna.com                                                               |                     |               |

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**WARNING:** BONDS SKIN IN SECONDS.  
COMBUSTIBLE LIQUID.  
CAUSES EYE IRRITATION.  
MAY CAUSE RESPIRATORY IRRITATION.  
SUSPECTED OF CAUSING CANCER.

| HAZARD CLASS                                     | HAZARD CATEGORY |
|--------------------------------------------------|-----------------|
| FLAMMABLE LIQUID                                 | 4               |
| EYE IRRITATION                                   | 2B              |
| CARCINOGENICITY                                  | 2               |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE | 3               |

### PICTOGRAM(S)



### Precautionary Statements

#### Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing, eye and face protection.

#### Response:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

IDH number: 229732

Product name: LOCTITE 426 BLACK INSTANT ADHESIVE known as 426 Prism® Black Max® Gel Inst

**Disposal:**

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|
| Ethyl 2-cyanoacrylate  | 7085-85-0  | 80 - 90     |
| Treated fumed silica   | 67762-90-7 | 1 - 5       |
| Carbon black           | 1333-86-4  | 1 - 5       |
| Hydroquinone           | 123-31-9   | 0.1 - 1     |
| Phthalic anhydride     | 85-44-9    | 0.1 - 1     |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation:</b>         | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Skin contact:</b>       | Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.                                                                                                                                                      |
| <b>Eye contact:</b>        | Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage. |
| <b>Ingestion:</b>          | Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.                                                                                                                                                                                                                                                                          |
| <b>Symptoms:</b>           | See Section 11.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Notes to physician:</b> | Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.                                                                                                                                                                                                                                                                     |

### 5. FIRE FIGHTING MEASURES

|                                         |                                                                                                                               |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>Extinguishing media:</b>             | Water spray (fog), foam, dry chemical or carbon dioxide.                                                                      |
| <b>Special firefighting procedures:</b> | Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode. |

**Unusual fire or explosion hazards:** Not available.

**Hazardous combustion products:** Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Ventilate area. Do not allow product to enter sewer or waterways.

**Clean-up methods:** Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

**Storage:** Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV                                                                                                                                                                                           | OSHA PEL                                                        | AIHA WEEL | OTHER |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|-----------|-------|
| Ethyl 2-cyanoacrylate  | 1 ppm STEL<br>0.2 ppm TWA<br>(Respiratory sensitization)<br>(Dermal sensitization)                                                                                                                  | None                                                            | None      | None  |
| Treated fumed silica   | 10 mg/m3 TWA<br>Inhalable dust.<br>3 mg/m3 TWA<br>Respirable fraction.                                                                                                                              | 15 mg/m3 TWA Total dust.<br>5 mg/m3 TWA<br>Respirable fraction. | None      | None  |
| Carbon black           | 3 mg/m3 TWA<br>Inhalable fraction.                                                                                                                                                                  | 3.5 mg/m3 PEL                                                   | None      | None  |
| Hydroquinone           | 1 mg/m3 TWA<br>(Dermal sensitization)                                                                                                                                                               | 2 mg/m3 PEL                                                     | None      | None  |
| Phthalic anhydride     | (SKIN) Inhalable fraction and vapor.<br>0.005 mg/m3 STEL<br>Inhalable fraction and vapor.<br>0.002 mg/m3 TWA<br>Inhalable fraction and vapor. (Respiratory sensitization)<br>(Dermal sensitization) | 2 ppm (12 mg/m3)<br>PEL                                         | None      | None  |

**Engineering controls:** Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eyeface protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

**Skin protection:**

Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                          |                                                                                                                            |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Physical state:                          | Gel                                                                                                                        |
| Color:                                   | Black                                                                                                                      |
| Odor:                                    | Sharp, Irritating                                                                                                          |
| Odor threshold:                          | 1 - 2 ppm                                                                                                                  |
| pH:                                      | Not applicable                                                                                                             |
| Vapor pressure:                          | < 0.2 mm hg                                                                                                                |
| Boiling point/range:                     | > 149 °F (> 65°C)                                                                                                          |
| Melting point/ range:                    | Not determined                                                                                                             |
| Specific gravity:                        | 1.05                                                                                                                       |
| Vapor density:                           | 3 Approximately                                                                                                            |
| Flash point:                             | 65 - 93 °C (149°F - 199.4 °F) Tagliabue closed cup                                                                         |
| Flammable/Explosive limits - lower:      | Not determined                                                                                                             |
| Flammable/Explosive limits - upper:      | Not determined                                                                                                             |
| Autoignition temperature:                | 485 °C (905°F)                                                                                                             |
| Flammability:                            | Not applicable                                                                                                             |
| Evaporation rate:                        | Not available.                                                                                                             |
| Solubility in water:                     | Polymerises in presence of water.                                                                                          |
| Partition coefficient (n-octanol/water): | Not applicable                                                                                                             |
| VOC content:                             | < 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)<br>< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated) |
| Viscosity:                               | Not available.                                                                                                             |
| Decomposition temperature:               | Not available.                                                                                                             |

## 10. STABILITY AND REACTIVITY

|                                   |                                                                                                    |
|-----------------------------------|----------------------------------------------------------------------------------------------------|
| Stability:                        | Stable under recommended storage conditions.                                                       |
| Hazardous reactions:              | Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols. |
| Hazardous decomposition products: | Not available.                                                                                     |
| Incompatible materials:           | Water, amines, alkalis and alcohols.                                                               |
| Reactivity:                       | Not available.                                                                                     |
| Conditions to avoid:              | Spontaneous polymerization.                                                                        |

## 11. TOXICOLOGICAL INFORMATION

|                              |                        |
|------------------------------|------------------------|
| Relevant routes of exposure: | Skin, Inhalation, Eyes |
|------------------------------|------------------------|

### Potential Health Effects/Symptoms

|                      |                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation:</b>   | Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.                                                                                                                                                                                                                     |
| <b>Skin contact:</b> | Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin. |
| <b>Eye contact:</b>  | Irritating to eyes. Causes excessive tearing. Eyelids may bond.                                                                                                                                                                                                                                                                                                                      |
| <b>Ingestion:</b>    | Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.                                                                                                                                                                                                                                                    |

| Hazardous Component(s) | LD50s and LC50s                                                                                                                                                                                                | Immediate and Delayed Health Effects                                                                                    |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Ethyl 2-cyanoacrylate  | None                                                                                                                                                                                                           | Irritant, Allergen, Respiratory                                                                                         |
| Treated fumed silica   | None                                                                                                                                                                                                           | Irritant                                                                                                                |
| Carbon black           | Oral LD50 (Rat) = > 8,000 mg/kg                                                                                                                                                                                | Respiratory, Some evidence of carcinogenicity                                                                           |
| Hydroquinone           | Oral LD50 (Rat) = 320 mg/kg<br>Oral LD50 (Mouse) = 245 mg/kg<br>Oral LD50 (Rabbit) = 540 mg/kg<br>Dermal LD50 (Rat) = > 900 mg/kg                                                                              | Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Immune system, Irritant, Liver, Mutagen, Skin, Thyroid |
| Phthalic anhydride     | Oral LD50 (Rat) = 800 mg/kg<br>Oral LD50 (Mouse) = 1,500 mg/kg<br>Oral LD50 (Rat) = 1,530 mg/kg<br>Oral LD50 (Rat) = 4,020 mg/kg<br>Oral LD50 (Rabbit) = > 1,000 mg/kg<br>Dermal LD50 (Rabbit) = > 3,160 mg/kg | Allergen, Corrosive, Irritant, Respiratory                                                                              |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|------------------------|----------------|-----------------|------------------------------------------|
| Ethyl 2-cyanoacrylate  | No             | No              | No                                       |
| Treated fumed silica   | No             | No              | No                                       |
| Carbon black           | No             | Group 2B        | No                                       |
| Hydroquinone           | No             | No              | No                                       |
| Phthalic anhydride     | No             | No              | No                                       |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

|                                  |                                                  |
|----------------------------------|--------------------------------------------------|
| <b>Proper shipping name:</b>     | Combustible liquid, n.o.s. (Cyanoacrylate ester) |
| <b>Hazard class or division:</b> | Combustible Liquid                               |
| <b>Identification number:</b>    | NA 1993                                          |
| <b>Packing group:</b>            | III                                              |

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)  
**Hazard class or division:** 9  
**Identification number:** UN 3334  
**Packing group:** III  
**Exceptions:** Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

**Water Transportation (IMO/IMDG)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**15. REGULATORY INFORMATION****United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None above reporting de minimis  
**CERCLA/SARA Section 302 EHS:** Hydroquinone (CAS# 123-31-9).  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health, Fire, Reactive  
**CERCLA/SARA Section 313:** None above reporting de minimis.  
**CERCLA Reportable quantity:** Hydroquinone (CAS# 123-31-9) 100 lbs. (45.4 kg)  
**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Canada Regulatory Information**

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**16. OTHER INFORMATION**

**This safety data sheet contains changes from the previous version in sections: 2**

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 11/01/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.